

4M COMPACT PTZ DOME CAMERA

x4



VVK-NSZ41X04

Specification

CAMERA

Image Sensor	1/1.8" Progressive Scan CMOS
Image Size	2560x1440
Shutter Speed	1/5s to 1/20000s
Min. Illumination	Color: 0.001 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
IR Distance	20M
Lens	2.8-12mm @ F No. 1.8 (W) ~ 3.3(T) H: 114.6(W) - 48.3(T)° V: 59(W) - 27.1(T)° D : 141.6(W) - 55.5(T)°

PTZ

Pan Range	350°
-----------	------

VIDEO IMAGE

Video Compression	H.264 / H.265
Resolution	4MP(2560x1440), 3MP(2304x1296), 1080P(1920x1080), 720P(1280x720), VGA(640x480), QVGA(320x240) @ 50/60 Hz

NETWORK / INTERFACE

Network	RJ45(10/100BASE-T)
Network Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Interface Protocol	ONVIF (Profile S/G/T)
Web Browser	Microsoft Edge, Safari, Firefox, Google Chrome
Storage	Built-in micro SD card slot, up to 256GB
Video Output	No
Audio	Built-in MIC / Built-in speaker
Alarm	N/A
Hardware Reset	Yes

FUNCTIONS

Smart Alarm	Motion detection Face Recognition (FR) Human&Vehicle Detection (PD&VD) Perimeter Intrusion Detection (PID) Line Crossing Detection (LCD) Cross Counting (CC) Stationary Object Detection (SO D) Heat Map (HM) Crowd Density Detection (CD) Queue Length Detection (QD) license Plate Detection (LPD) Rare Sound Detection (RSD)
Smart Analytics	

GENERAL

Power Supply	D12V/POE(IEEE802.3af)
Power Consumption	N/A
Operating Environment	-30 °C to 55 °C
Dimensions	Ø153 X 118.8 mm
Weight	Approx. 952g
Ingress Protection	IP66, IK10

Feature

- 4MP (2560 x 1440) @ 30fps
- Max. resolution: 2560 x 1440
- Supports Smart H.265/H.264 encoding
- True Day & Night
- Up to 0.002 Lux Sensitivity
- 20M IR Distance
- 4X Optical Zoom
- 3D DNR, True WDR, HLC, BLC and ROI encoding
- 350° Endless Pan
- 1 channel Audio input; 1 channel Audio output
- DC 12V/PoE
- IP66 Ingress Protection

Dimension

