

## HD-SDI IR NIGHT VISION CAMERA - VVK-CIE66HVD

### Key Features

- 1/3" 2M Pixels Progressive Sensor
- High Resolution 1100 TV Lines
- 1080P(30P,25P) , 720P(60P,50P)
- Privacy Mask Function
- Day & Night Function
- WDR, BLC, ACE, HLC Function
- OSD Control
- Varifocal Lens 2.8~12mm DC Auto Iris Filter Removable
- Power DC12V(Option - DC12V / AC24V)
- Analog External Video Out(BNC Jack)
- RS-485 Communication(Protocol Selectable)



Photo

MODEL	VVK-CIE66HVD
Image Sensor	1/3" SONY CMOS Sensor
Total Pixels	2010(H) x 1108(V), 2.2Mega Pixels
Active Pixels	1944(H) x 1092(V), 2.1Mega Pixels
Scanning System	Progressive
Resolution	Digital : 1920x1080p(1080p / 30fps) , 1280x720p(720p / 60fps) Analog : 700TVL
Minimum Illumination	Min. Illumination 0.1Lux(IR LED Off) / 0.0000Lux(IR LED On)
Video Output	HD : HD-SDI Analog : NTSC, PAL(Without WDR)
S/N Ratio	More than 50dB(AGC Off)
Shutter Speed	Auto / Manual(1/30(1/25) ~ 1/60000)
Day & Night	Auto / Day / Night / EXT
Lens	Varifocal Lens 2.8~12mm DC Auto Iris Filter Removable
Protocol	VISCA, Pelco-D, Pelco-P
Baud Rate	2400 ~ 115200 bps
White Balance	Auto / One Push / Manual / Indoor / Outdoor
DSS	Off, X2, X3, X4
DNR	Off / Low / Middle / High / Auto
WDR/BLC	Off / WDR / BLC
Privacy Mask	Off / On
Motion	Off / On
Language	English
IR LED	Visible 5mm Diameter(850nm, 30 °) x 66pcs
Visibility Range	Indoor 55m / Outdoor 40m
Power Input	DC 12V ±10% / 1.5A(Option - DC12V / AC24V)
Power Consumption	DC 12V / 750mA
Operating Temperature	-10 °C ~ +50 °C
Operating Humidity	Less than 90%
Dimension	145(W) x 104(H) x 350(D)mm
Weight	Approx. 1200(g)