

AHD DVR - VVK-0402L / VVK-0815L / VVK-1623L



MODEL		VVK-0402L	VVK-0815L	VVK-1623L	
Description		Analog HD/960H Hybrid DVR			
Video	Input	Number of Channels	4	8	16
		CCTV Camera	AHD (720p25/30) or 960H		
	Output	Main Monitor	HDMI and VGA		
		Sub Monitor	None	None	None
Audio	Input / Output		4 / 1	4 / 1	4 / 1
	Audio Codec		G.711		
Alarm	Sensor Input		4	4	4
	Alarm Output		1	1	1
		RS-485	1		
Recording	Compression		H.264 (Main Profile)	H.264 (High Profile)	
	1280x720 AHD Camera Input	1280x720	15fps/ch		
		640x360	15fps/ch		
	Analog Camera Input	960H	25/30fps/ch		
		D1	25/30fps/ch		
		CIF	25/30fps/ch		
	Recording Quality Grade		5 Levels		
	Recording Mode		Continuous / Motion / Sensor / Schedule / Manual		
	Pre Recording		Max. 20 Minutes		
Post Recording		Max. 60 Seconds			
Playback	Search		Date/Time, Event, Archive, Log		
	Multi-Decoding		1, 4	1, 4, 8	1, 4, 9, 16
	Playback Speed		x0.25, x0.5, x2, x4, x8, x16, x32, x64		
Backup	Media		USB drive, External HDD, Network		
	Format		BMP, AVI, Proprietary Format		
	Huge Backup		Yes (Max. 24 hours)		

Storage	HDD	Capacity of 1 HDD	4TB		
		Internal HDDs	1	1	1
		e-SATA	None	None	None
	USB	Front	None		
		Rear	2		
User I/F	Input Method	IR, Mouse, Keyboard Controller			
Network	Network Interface	10/100 Base-T			
	Dynamic DNS	Yes (Free DDNS)			
	Dual Encoding for Network	Yes			
Features	Digital Zoom	Yes			
	DLS (Day Light Saving)	Yes			
	NTP (Network Time Protocol)	Yes			
	S.M.A.R.T	Yes			
	Internal Beep	Yes			
	Multi-Language	Yes			
	e-mail Notification	Yes			
Network Access	3G Mobile	iPad / iPhone / Android			
	Web Viewer	Windows (IE, Chrome, Firefox, Safari)			
	PC Client	Single / Multi Client and CMS (64 channels)			
	Remote Setup and Upgrade	Yes			
Power	Power Supply Voltage	DC 12V 2A	DC 12V 2A	DC 12V 5A	
Temperature	Operation	5°C ~ 40°C			
	Storage	-10°C ~ 50°C			
Humidity	Operation	20% ~ 80% (Non-condensing)			
Weight	Unit Weight (Gross weight)	2KG	2KG	2KG	
Dimension	Unit Dimension (W x H x D)	300mm x 53mm x 227mm	300mm x 53mm x 227mm	300mm x 53mm x 227mm	