

HD-SDI IR PLASTIC DOME CAMERA - VVK-2200IR

Key Features

- 1/3" Panasonic CMOS
- HD Resolution : 1080P 30fps
- 1080P(30P,25P) , 720P(60P,50P)
- WDR (Wide Dynamic Range)
- DNR (Digital Noise Reduction : 2D + 3D)
- Privacy Mask Function
- Intelligent Motion Detection
- Defog : Defogging foggy video image
- 2.8 ~ 12mm Varifocal Mega Pixel Lens
- OSD Control (Option)
- EX-SDI(Extendsd HD-SDI)
- Power DC12V
- Analog External Video Out(RCA Jack) (Option)



SDI MODE CHANGE	
HD-SDI → EX-SDI	handle lift direction 3times, press enter
EX-SDI → HD-SDI	handle right direction 3times, press enter

MODEL	VVK-2200IR
CMOS Device	1/3" Panasonic CMOS
Total Pixels	1956(H) x 1266(V), 2.5Mega Pixels
Active Pixels	1944(H) x 1092(V), 2.1Mega Pixels
Scanning System	Progressive
Resolution	Digital : 1920x1080p, 1280x720p Analog : 700TVL
Minimum Illumination	Color : 1.0 lux, BW : 0.5lux Color DSS : 0.002 lux BW DSS : 0.001 lux
Video Output	HD-SDI, EX-SDI, CVBS
	Analog : NTSC / PAL(Without WDR)
S/N Ratio	More than 50dB(AGC Off)
Shutter Speed	Auto / Manual(1/30 ~ 1/30000) FLICKER
E.Zoom	x1 ~ x16
Day & Night	Auto / Color / B&W / Ext
Lens	2.8 ~ 12mm Varifocal Mega Pixel DC Lens
White Balance	Auto / Auto Ext / Preset / Manual
DNR	Off / Low / Middle / High
WDR / BLC / HLC	Off / WDR(Low / Middle / High) / BLC / HLC
Defog	Off / On
Privacy Mask	16 Mask
Motion Detection	Off / On (16 Points)
Language	ENG / KOR / CHN / CHN(S) / JPN
IR LED	Visible 5mm Diameter(850nm, 30 °) x 30pcs
Visibility Range	Indoor 20m / Outdoor 15m
Power Input	DC 12V ±10% / 1A
Power Consumption	DC 12V / 450mA
Operating Temperature	-10 °C ~ +50 °C
Operating Humidity	Less than 90%
Dimension	100(Φ) x 100(H) x 130(D)mm
Weight	Approx. 350(g)